

## PARAFON Buller Mesh



Certification Number

0809-CPR-1013 / Eurofins Expert Services Ltd, P.O. Box 1001, FI-02044 VTT, Finland

Short Description

PARAFON Expanded Metal Cassette is an integrated acoustic panel for exposed locations and environments. The surface protection consists of expanded metal made of galvanised sheet around a PARAFON Buller acoustic panel made of non-combustible mineral wool with the highest fire classification, A1, in accordance with EN 13501-1.

Application

The product is particularly suitable for areas where the acoustic panels are also required to have good mechanical durability. For example industrial areas and sports centres

Usage Conditions

May be used continuously in 95 % relative humidity at a temperature of 30 °C, occasionally also at 100 % and 40 °C.

### Dimensions

Dimensions		
Thickness	Width x Length	Weight
Edge A: 50 mm	600 x 1795 mm	7,5 kg/m <sup>2</sup>

Fixed sizes

### Packaging

Package Type

Pall

### Fire Properties

#### Reaction to Fire

Property	Value	According to
Reaction to Fire, Euroclass	A1	EN 13964:2014 (EN 13501-1)

#### Other Fire Properties

Property	Value	According to
Combustibility	Base product non-combustible	EN ISO 1182

### Sound Properties

#### Acoustic Absorption Index

Property	Value	According to
Sound Absorption $\alpha_w$ , Direct Fixing	0.90	EN 13964:2014 (EN ISO 354 / EN ISO 11654)

Property	Value	According to
Practical Sound Absorption Class	A	EN 13964:2014 (EN ISO 354 / EN ISO 11654)

### Mechanical Properties

#### Tensile/Flexural Strength

Property	Value	According to
Flexural Tensile Strength	NPD	EN 13964:2014

#### Other Mechanical Properties

Property	Value	According to
Shatter Properties	NPD	EN 13964:2014

### Emissions

Property	Value	According to
Emission Indoor Climate	M1	Finnish Classification

#### Release of Dangerous Substances to the Indoor Environment

Property	Value	According to
Release of Formaldehyde	E1	EN 13964:2014
Release of Asbestos	No content of asbestos	EN 13964:2014

### Durability


Durability of Reaction to Fire Against Heat, Weathering, The fire performance of mineral wool does not deteriorate with time. The Ageing/Degradation does not deteriorate with time. The Euroclass classification of product is related to the organic content, which cannot increase with time.

### Facings

#### Facing Material

Expanded metal netting with acoustic panel – Natural, White or Black – behind. Back side: Thin glass fiber tissue.

#### Colours



Natural grey, NCS



White, NCS S 1000-N



Black, NCS S 9000-N

#### Edges

##### Treatment of Edges

On the long sides, the expanded metal is bent over the edge to the back of the panel, and there is a metal sheet under the grid to reinforce the edges.

#### Installation

Installation to wall either horizontally or vertically with profiles.

#### Maintenance

Dry cleaning using a soft brush or by vacuum cleaning. Wet cleaning by wiping with a damp cloth or sponge.

#### Disposal and Recycling

May be used as thermal insulation or taken to a dump. No restrictions.

Head Office: PAROC GROUP, P.O. Box 240 (Energiakuja 3), FI-00181 Helsinki Finland, Tel. +358 46 876 8000, [www.paroc.com](http://www.paroc.com)

The information in this brochure describes the conditions and technical properties of the disclosed products, valid at the time of publication of this document and until replaced by the next printed or digital version. The latest version of this brochure is always available on the Paroc website. Our information material presents applications for which the functions and technical properties of our products have been approved. However, the information does not mean a commercial guarantee. We do not assume liability of the use of third party components used in the application or the installation of our products. We cannot warrant the suitability of our products if used in an area or conditions which are not provided in our information material. As a result of constant further development of our products we reserve the right to make alterations to our information material at any time. PAROC is a registered trademark of Paroc Group. This data sheet is valid in following countries: international use (general information).