Prelude T-15 XL²

Short Description	Suspended ceilings. Top quality Exposed 15 mm T-grid system. Fire punched, made of galvanized steel and coated with white paint. Less visible than T24 profiles in edge A installations or to be used with E15-edged ceiling tiles.

Dimensions

Dimensions	
Width x Length	**Height**
Universal Main runner Prelude 15 Peakform:	
15 x 3600 mm (White)	43 mm
.	
Cross tee Prelude 15 XL²:	
15 x 1200 mm (White)	38 mm
15 x 600 mm (White)	38 mm
.	
Perimeter trim:	
22 x 3000 mm (White)	22 mm
.	
Shadowline:	
(15+15) x 3050 mm (White)	(8 + 25) mm

Packaging

Package Type	Carton

Fire Properties

Reaction to Fire		
Property	**Value**	**According to**
Reaction to Fire, Euroclass	A1	EN 13964:2014

The grid is able to cope with expansion due to heat in a fire and remain flat and stable so that no large caps and cracks appear between grid and tile.

Mechanical Properties

Other Mechanical Properties		
Property	**Value**	**According to**
Durability	Corrosion protection class B	EN 13964:2014

Paroc Group © 2020

Facings

Facing Material	Baked polyester paint

Colours

Global white, nearest RAL 9003/NCS 0502-B

Maintenance

Clean with mild household cleaner and a soft cloth. Before cleaning the grid remove the ceiling tiles to prevent cleaning solution or dirt from getting on the tiles.

Paroc Group © 2020